Schindler 5500 MRL

A ceiling not just for the eyes. Ambiance too.





Ceilings

Your suspended ceiling will have striking spot LED downlights.

- One panel is used in cars with 2100 lb., 2500 lb. and 3000 lb. capacities
- Two panels are used in 3500 lb., 4000 lb., 4500 lb. and 5000 lb. capacities.





Exista LED Spot Technical Data

Luminous output: 480lm
Color temperature: 4100K
Socket: GU5.3 MR16
Average lamp lifetime L70: 30000h
Angle of radiation: 80°
Dimension (ø x H): ø 50mm x 40mm



Accessories

Counterweights

ties

Safet

Fixtures

Cars

Doors

Alw Aechanical Naterial

Controls

DR Drives



Schindler 5500 MRL Ceiling dimensions and arrangement

General Purpose Car Ceilings

		Ceiling Dimensions*		
Capacity lbs (kg)	Car Size	Width A in (mm)	Depth B in (mm)	Ceiling/Fixture Arrangement
2100 (950)	69.0" x 51.63" STD	5′-7″ (1702)	4'-3 ⁵ /8" (1311)	
	68.5" x 51.50" RDC	5'-6 ¹ /2" (1689)	4'-3 ¹ /2" (1308)	
2500 (1135)	(CS) 84.38" x 51.63"STD	6'-10 ³ /8" (2092)	4'-3 ⁵ /8" (1311)	O O O O O O O O O O O O O O O O O O O
	GP 76.63" x 51.50" RDC	6'-2 ⁵ /8" (1896)	4'-3 ¹ /2" (1308)	Ceiling
3000 (1360)	(S) 84.38" x 56.13" STD	6'-10 ³ /8" (2092)	4'-8 ¹ / ₈ " (1426)	Ceiling Width
	(CS) 76.63" x 60.38"RDC	6'-2 ⁵ /8" (1896)	5'-0 ³ /8" (1534)	
3500 (1590)	(S) 84.38" x 64.0" STD	6'-10 ³/s" (2092)	5'-2" (1575)	
	(S) 76.63" x65.38" RDC	6'-2 ⁵ /8" (1896)	5'-3 ³ /8" (1610)	0 0 0
	(S) 80.75" x 70.88" RDC	6'-6 ³ / ₄ " (2000)	5′-8 ⁷ /8″ (1750)	0 0 0
4000 (1815)	88.63" x 65.38" RDC	7'-2 ⁵ /8" (2200)	5'-3 ³ /8" (1610)	Ceiling Width
	96.13" x 64.0" STD	7'-10 ¼8" (2391)	5'-2" (1575)	0 0 0 0 0 0
				A—————————————————————————————————————

^{*}Dimensions may change depending on the car deco thickness selected.

Note

Dimensions and configurations are for our standard cabs. For flexible sizing please contact your local Schindler representative.

Hospital/Service Car Ceilings

Capacity lbs (kg)	Car Size	Width A in (mm)	Depth B in (mm)	Ceiling/Fixture Arrangement
4000 (1815)	72.50″x86.63″ STD	5'-10 ¹/2" (1794)	7'-0 ⁵ /8" (2150)	o o o B Ceiling Depth
4000 (1815)	64.38″x92.63″ RDC	5'-2 ³ /8" (1584)	7'-6 ⁵ /s" (2302)	Ceiling Width
4500 (2040) -	72.5"x 92.63" STD	5′-10 ¹/₂" (1791)	7'-6 ⁵ /8" (2302)	0 0 0
	64.38"x100.50" RDC	5'-2 ³ /8" (1584)	8'-2 ¹ / ₂ " (2502)	Ceiling Depth
5000 (2270) -	AIA 69"x108.38" STD	5'-7" (1584)	8'-10 ³/8" (2702)	O O O
	64.38"x107.88" RDC	5'-2 ³ /8" (1584)	8'-9 ⁷ / ₈ " (2689)	
	72.5"x100.50" STD	5′-10 ¹/₂″ (1791)	8'-2 ¹ / ₂ " (2502)	Ceiling Width

 $[\]mbox{^*Dimensions}$ may change depending on the car deco thickness selected.

Note

Dimensions and configurations are for our standard cabs. For flexible sizing please contact your local Schindler representative.

Schindler 5500 MRL Elevator ceiling

For further information, including location of the Schindler office nearest you, please contact:

U.S. Headquarters. Morristown, New Jersey Toll-Free 877.696.8382

www.us.schindler.com

Canada Headquarters. Toronto, Ontario Tel. 416.332.8280

www.ca.schindler.com



Schindler is a member organization of the U.S. Green Building Council.



Schindler has received renewal to ISO 14001:2004 and ISO 9001:2008 certificates.



Schindler prints with vegetable-based ink on paper containing post-consumer waste fiber.